



"OL-50 spray" - ref 2065

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : "OL - 50 " vegetable solvent cleaner

Product code : 2065

1.2. Relevant identified uses of the substance or mixture and uses advised against

Cleans brushes, tools, glue marks and tar.

1.3. Details of the supplier of the safety data sheet

Registered company name : ActiNa srl

Address : Avenue Thomas Edison, 182 B- 1402 Nivelles Belgium.

Telephone : +32 (0) 67 87 81 00 Fax : /.

info@galtane.com

https://www.galtane.com

1.4. Emergency telephone number : +32 (0) 67 87 81 00

Hours of operation : Monday - Friday : 8:00-16:00

Other emergency numbers

Belgique / België : tel. 070 245 245 ; Netherlands : tel. 030 274 88 88 ; Suisse : tél. 044 251 66 66 ; Luxembourg : tél. 8002-5500 ; France : tél. 01 40 05 48 48

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

This mixture does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

The propellant gas is not taken into account when determining the health and environmental classification of the mixture.

2.2. Label elements

Detergent mixture (see section 15).

Mixture for aerosol application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02

Signal Word :

DANGER

Hazard statements :

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements - Prevention :

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

Precautionary statements - Storage :

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

OL - 50 spray ref. 2065**2.3. Other hazards**

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances $\geq 0.1\%$ with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

Intentional misuse of the preparation by concentrating and inhaling the vapours can be harmful or fatal.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	Classification (EC) 1272/2008	Note	%
CAS: 106-97-8 EC: 203-448-7 REACH: 01-2119474691-32-XXXX BUTANE (< 0,1 % 1,3-BUTADIENE)	GHS02 Dgr Flam. Gas 1A, H220 Press. Gas, H280	C [1] [7]	10 \leq x % < 25
CAS: 74-98-6 EC: 200-827-9 REACH: 01-2119486944-21-XXXX PROPANE	GHS02 Dgr Flam. Gas 1A, H220 Press. Gas, H280	[1] [7]	2.5 \leq x % < 10

Information on ingredients :

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

[7] Propellant gas

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures**In the event of exposure by inhalation :**

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

In the event of splashes or contact with skin :

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice (show the label if possible). If symptoms persist, always call a doctor.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

If the aerosols are exposed to a fire : keep containers cool by spraying with water from a protected position.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist

- water with AFFF (Aqueous Film Forming Foam) additive

OL - 50 spray ref. 2065

- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

In a fire or if heated, a pressure increase will occur and the container may burst. Bursting aerosol containers may be propelled from a fire at high speed. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

If possible, stop the product stream. Spray from a protected position till the containers are cool. If possible, take the aerosols outside. Keep public at a distance.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

OL - 50 spray ref. 2065**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Storage in a dry, frost-free and well ventilated place.

Store upright.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limits :**

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	600 ppm 1450 mg/m3	750 ppm 1810 mg/m3		Carc	

- Ireland (Code of practice for the Chemical Agents Regulations, 2021) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8		1000 ppm			
74-98-6				Asphx.	

8.2. Exposure controls**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

Do not spray in the direction of the eyes.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

Not necessary at efficient use. Wash your hands after contact with skin.

- Body protection

OL - 50 spray ref. 2065

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

Not necessary at efficient use. Wash skin that has been in contact with the product, with water and soap.

- Respiratory protection

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

Do not breathe spray. Use only in well-ventilated areas.

Exposure controls linked to environmental protection

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state

Physical state : Fluid liquid.
Spray.

Colour

Light yellow, clear

Odour

Odour threshold : Not stated.
Odour : Specific

Freezing point

Freezing point / Freezing range : Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range : Not relevant.

Flammability

Flammability (solid, gas) : Not stated.
Flammability : Extremely flammable

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) Not stated.
:
Explosive properties, upper explosivity limit (%) Not stated.
:

Flash point

Flash point interval : Not relevant.

Auto-ignition temperature

Self-ignition temperature : Not relevant.

Decomposition temperature

Decomposition point/decomposition range : Not relevant.

pH

pH (aqueous solution) : Not stated.
pH : Not relevant.

Kinematic viscosity

Viscosity : Not stated.

Solubility

Water solubility : Insoluble.
Fat solubility : Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water : Not stated.

Vapour pressure

Vapour pressure (50°C) : Not relevant.

Density and/or relative density

Density : 0.776

Relative vapour density

Vapour density : Not stated.

OL - 50 spray ref. 2065

Particle characteristics

The mixture does not contain nanoforms.

9.2. Other information

VOC (g/l) :	194.00
Pressure at 20°C :	± 3.5 bar
Pressure at 50°C :	< 10 bar
Water content :	< 0.3 % w/w

9.2.1. Information with regard to physical hazard classes

No data available.

Aerosols

Chemical combustion heat :	Not specified.
Inflammation time :	Not specified.
Deflagration density :	Not specified.
Inflammation distance :	Not specified.
Flame height :	Not specified.
Flame duration :	Not specified.

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heat
- flames and hot surfaces
- frost

Protect from sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat and sources of ignition. Storage in a dry, frost-free and well ventilated place.

10.5. Incompatible materials

No materials known by which a dangerous reaction can occur.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

The product is stable. Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Splashes in the eyes may cause irritation and reversible damage

11.1.1. Substances

Acute toxicity :

PROPANE (CAS: 74-98-6)	
Inhalation route (Dusts/mist) :	LC50 > 10 mg/l

BUTANE (< 0,1 % 1,3-BUTADIENE) (CAS: 106-97-8)	
Inhalation route (Vapours) :	LC50 > 10 mg/l

OL - 50 spray ref. 2065

Skin corrosion/skin irritation :

Butane/Isobutane/Propane : Based on available data, the classification criteria are not met.

Serious damage to eyes/eye irritation :

Butane/Isobutane/Propane : Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation :

Butane/Isobutane/Propane : Based on available data, the classification criteria are not met.

Germ cell mutagenicity :

PROPANE (CAS: 74-98-6)

No mutagenic effect.

BUTANE (< 0,1 % 1,3-BUTADIENE) (CAS: 106-97-8)

No mutagenic effect.

Carcinogenicity :

PROPANE (CAS: 74-98-6)

Carcinogenicity Test :

Negative.

No carcinogenic effect.

BUTANE (< 0,1 % 1,3-BUTADIENE) (CAS: 106-97-8)

Carcinogenicity Test :

Negative.

No carcinogenic effect.

Reproductive toxicant :

PROPANE (CAS: 74-98-6)

No toxic effect for reproduction

BUTANE (< 0,1 % 1,3-BUTADIENE) (CAS: 106-97-8)

No toxic effect for reproduction

Specific target organ systemic toxicity - single exposure :

Butane/Isobutane/Propane : Based on available data, the classification criteria are not met.

Specific target organ systemic toxicity - repeated exposure :

Butane/Isobutane/Propane : Based on available data, the classification criteria are not met.

Aspiration hazard :

Butane/Isobutane/Propane : Not applicable to gases and gas mixtures.

11.1.2. Mixture

No toxicological data available for the mixture.

11.2. Information on other hazards

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

PROPANE (CAS: 74-98-6)

Biodegradability :

Rapidly degradable.

BUTANE (< 0,1 % 1,3-BUTADIENE) (CAS: 106-97-8)

Biodegradability :

Rapidly degradable.

12.3. Bioaccumulative potential

Butane/Isobutane/Propane : Not expected to be dangerous for the aquatic environment.

12.4. Mobility in soil

Butane/Isobutane/Propane : If released into the environment, the product will rapidly disperse into the atmosphere where it will undergo photochemical degradation.

OL - 50 spray ref. 2065

12.5. Results of PBT and vPvB assessment

Butane/Isobutane/Propane : Not considered to be a PBT or a vPvB.

12.6. Endocrine disrupting properties

Butane/Isobutane/Propane : Not applicable.

12.7. Other adverse effects

Butane/Isobutane/Propane : Not applicable.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Recycle or dispose of waste in compliance with current legislation, namely the Ordinance on the Avoidance and Disposal of Waste (Waste Ordinance, VVEA, SR 814.600), the Ordinance on Waste from June 22, 2005 (VeVA, SR 814, 610) and DETEC Ordinance on Waste Lists.

Disposal of the product (the unused product, residual quantities, the cured product, emptied but uncleaned packaging) : preferably by an approved waste collector or a specialist disposal company. Suitable containers and methods of waste treatment should be used.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

15 01 10 * packaging containing residues of or contaminated by dangerous substances

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2023 - IMDG 2022 [41-22] - ICAO/IATA 2023 [64]).

14.1. UN number or ID number

1950

14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

14.3. Transport hazard class(es)

- Classification :

2.1

ADR/RID Label : Limited Quantity : 2.1 is not applicable.

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation	
	2	See SP63	-	See SP277	F-D. S-U	63 190 277 327 344 381 959	E0	- SW1 SW22	SG69	
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	2.1	-	-	203	75 kg	203	150 kg	A145 A167 A802	E0	
	2.1	-	-	Y203	30 kg G	-	-	A145 A167 A802	E0	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

OL - 50 spray ref. 2065

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

Container information:

No data available.

Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):
<https://echa.europa.eu/substances-restricted-under-reach>.

Explosives precursors :

The mixture does not contain any substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors.

Particular provisions :

No data available.

Labelling for detergents (EC Regulation No. 648/2004,907/2006) :

- 15 % or over but less than 30 % : aliphatic hydrocarbons

15.2. Chemical safety assessment

The product does not contain substances for which a chemical safety assessment has been performed.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

Abbreviations and acronyms :

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.